

DI

1/1 - (C) FILE CAPLUS
 AN - 1983:527512 CAPLUS XP-002277299
 DN - 99:127512
 ED - Entered STN: 12 May 1984
 TI - Concrete
 PA - Showa Denko K. K., Japan
 SO - Jpn. Kokai Tokkyo Koho, 5 pp.
 CODEN: JKXXAF
 DT - Patent
 LA - Japanese
 IC - C04B13/00;C04B13/21
 CC - 58-2 (Cement, Concrete, and Related Building Materials)
 Section cross-reference(s): 60

FAN.CNT 1

	PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
PN	JP58079859	A	19830513	JP 1981-174436	19811102
PR	JP 1981-174436			19811102	
AB	Aq. slurries contg. hydraulic cement and Ca aluminates are mixed with cement-contg. wastewater, sludges, sludge powder, and/or slurries to make concrete. Thus, portland cement 46.9, silica sand 31.3, Ca(OH) ₂ 1.8, water 23.0, and Na citrate [994-36-5] 0.3 part were mixed with cement-contg. sludge 28.6 parts, a foaming agent, and a mixt. of Al ₂ O ₃ cement 10 and water 7 parts to make lightwt. air-entrained concrete with bending strength 13.0 and compact strength 76.5 kg/cm ² . → 50 kg/cm ²				
ST	calcium aluminate concrete; alumina cement concrete				
IT	Slimes and Sludges (cement, in concrete batches for air-entrained lightwt. concrete)				
IT	Concrete (lightwt., air-entrained, cement sludge and calcium hydroxide and sodium citrate in raw mixes for)				
IT	994-36-5 1305-62-0, uses and miscellaneous RL: USES (Uses) (in concrete batches, contg. cement sludges, for lightwt. air-entrained concrete)				

snellie wahardi,